WBPS

POWER YOU CAN TRUST

CONTAINERISED J33

ENGINE CHARACTERISTICS

BENEFITS

- Upto 100kVA
- Large internal fuel tank
- Integrated distribution unit
- Internal LED lighting
- Available with remote monitoring
- Available as hybrid package
- Reduced acoustic levels
- Completely self contained

POPULAR FOR

- Construction sites
- Utilities sector
- Telecoms industry
- Highway applications
- Remote locations

POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

TERMS OF USE

According to the standard, the nominal power assigned by the genset is given for 25°C Air Intlet Temperature, of a barometric pressure of 100 kPA (100 m A.S.L), and 30 % relative humidity. For particular conditions in your installation, refer to the derating table.

GENERAL CHARACTERISTICS	
Frequency (Hz)	50
Voltage (V)	400/230
Standard Control Panel	APM303

POWER					
Voltage	ESP		PRP		Standby Amps
	kWe	kVA	kWe	kVA	
220 TRI	26	33	24	30	87
	25	31	23	28	43
	26	33	24	30	48
	26	33	24	30	50
	26	33	24	30	95
240 TRI	26	33	24	30	79
230 TRI	26	33	24	30	83

OVERALL DIMENSIONS	
Length (mm)	2400
Width (mm)	3000
Height (mm)	2700
Dry weight (kg)	2750
Tank capacity (L)	1350

CONTACT US

WB Power Services Ltd, Heanor Gate Road
Heanor Gate Industrial Estate, Heanor
Derbyshire DE75 7RJ

Email us at: sales@wbpsltd.co.uk
Call us 01159 444 422
www.wbpsltd.co.uk/hire

WBPS

POWER YOU CAN TRUST

CONTAINERISED J33

ENGINE CHARACTERISTICS

GENERAL ENGINE DATA	
Engine model	JOHN DEERE
Engine ref.	3029DFS29
Air inlet	Athmo
Cylinders arrangement	L
Number of cylinders	3
Displacement (C.I.)	2.91
Air coolant	
Bore (mm) x Stroke (mm)	106 x 110
Compression ratio	17.2 : 1
Speed (RPM)	1500
Pistons speed (m/s)	5.5
Maximum stand-by power at rated RPM (kW)	31
Frequency regulation (%)	+/- 2.5%
BMEP (bar)	7.42
Governor type	Mechanical

COOLING SYSTEM	
Radiator & Engine capacity (L)	16.10
Max water temperature (°C)	105
Outlet water temperature (°C)	93
Fan power (kW)	0.70
Fan air flow w/o restriction (m3/s)	1.74
Available restriction on air flow (mm Water Column)	20
Type of coolant	Glycol-Ethylene
Thermostat (°C)	82-94

EXHAUST	
Exhaust gas temperature (°C)	555
Exhaust gas flow (L/s)	78
Max. exhaust back pressure (mm EC)	625

FUEL	
Consumption @ 110% load (L/h)	8.50
Consumption @ 100% load (L/h)	7
Consumption @ 75% load (L/h)	5
Consumption @ 50% load (L/h)	3.60
Maximum fuel pump flow (L/h)	111

OIL	
Oil capacity (L)	6
Min. oil pressure (bar)	1
Max. oil pressure (bar)	5
Oil consumption 100% load (L/h)	0.0070
Carter oil capacity (L)	5.30

HEAT BALANCE	
Heat rejection to exhaust (kW)	31
Radiated heat to ambiant (kW)	6
Heat rejection to coolant (kW)	18

AIR INTAKE	
Max. intake restriction (mm EC)	300
Intake air flow (L/s)	28

CONTACT US

WB Power Services Ltd, Heanor Gate Road
Heanor Gate Industrial Estate, Heanor
Derbyshire DE75 7RJ

Email us at: sales@wbpsltd.co.uk
Call us 01159 444 422
www.wbpsltd.co.uk/hire

CONTAINERISED J33
ALTERNATOR CHARACTERISTICS

GENERAL DATA	
Alternator ref.	AT00840T
Number of Phase	Three phase
Power factor (Cos Phi)	0.80
Altitude (m)	0 to 1000
Overspeed (rpm)	2250
Number of pole	4
Capacity for maintaining short circuit at 3 in for 10 s	Yes
Insulation class	H
T° class, continuous 40°C	H / 125°K
T° class, standby 27°C	H / 163°K
AVR Regulation	Yes
Total Harmonic Distortion in no-load DHT (%)	3.3
Total Harmonic Distortion, on load DHT (%)	2.1
Wave form : NEMA=TIF	<45
Wave form : CEI=FHT	<2
Number of bearing	1
Coupling	Direct
Voltage regulation at established rating (+/- %)	+/- 1%
Recovery time (Delta U = 20% transcient) (ms)	
Indication of protection	IP 23
Technology	Without collar or brush

OTHER DATA	
Continuous Nominal Rating 40°C (kVA)	30
Standby Rating 27°C (kVA)	32.50
Efficiencies 100% of load (%)	88.10
Air flow (m3/s)	0.0880
Short circuit ratio (Kcc)	0.62
Direct axis synchro reactance unsaturated (Xd) (%)	165
Quadra axis synchro reactance unsaturated (Xq) (%)	71
Open circuit time constant (T'do) (ms)	930
Direct axis transcient reactance saturated (X'd) (%)	15.40
Short circuit transcient time constant (T'd) (ms)	46
Direct axis subtranscient reactance saturated (X''d) (%)	8.80
Subtranscient time constant (T"d) (ms)	12
Quadra axis subtranscient reactance saturated (X"q) (%)	19
Subtranscient time constant (T"q) (ms)	
Zero sequence reactance unsaturated (Xo) (%)	2.80
Negative sequence reactance saturated (X2) (%)	13.20
Armature time constant (Ta) (ms)	11
No load excitation current (io) (A)	0.60
Full load excitation current (ic) (A)	1.96
Full load excitation voltage (uc) (V)	
Engine start (Delta U = 20% perm. or 50% trans.) (kVA)	
Transcient dip (4/4 load) - PF : 0,8 AR (%)	
No load losses (W)	
Heat rejection (W)	3242
Unbalanced load acceptance ratio (%)	

APM303, comprehensive and simple

The APM303 is a versatile unit which can be operated in manual or automatic mode. Equipped with an LCD screen, the user-friendly APM303 offers high-quality basic functions to guarantee simple, reliable operation and supervision of your generating set. It offers the following features:

Measurements: phase-to-neutral and phase-to-phase voltages, active power currents, effective power, power factors, Kw/h energy meter Fuel, oil pressure and coolant temperature levels

Supervision: Modbus RTU communication on RS485

Reports: 2 configurable reports

Safety features:
Overspeed, oil pressure
Coolant temperatures
Minimum and maximum voltage
Minimum and maximum frequency
Maximum current
Maximum active power
Phase sequence

Traceability:
Stack of 12 stored events For further information, please refer to the data sheet for the APM303.